



1.181 Inch | 30 Millimeter x 1.5 Inch | 38.1
Millimeter x 1.689 Inch | 42.9 Millimeter TIMKEN
YAS 30 SGT Pillow Block Bearings

Bearing No. YAS 30 SGT

YAS 30 SGT Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	1.465
EAN	0087796265561
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	12 Millimeter
Relubricatable	Yes
Insert Part Number	GYE30KRRB
Seals	Double Land Riding Rubber Contact
Housing Configuration	1 Piece Solid
Inch - Metric	Metric
Other Features	Single Row Spherical Normal Duty High Base Black Housing Powder Coated Epoxy Finish
Long Description	2 Bolt Pillow Block; 30MM Bore; 42.9MM Base to



Jinan Chenyu Bearing Import & Export ...

	Center Height; Set Screw Mount; Ball Bearing; 93.7MM Minimum Bolt Spacing; 141.3MM Bolt Spacing Maximum; Relubricatable; Cast Iron; Double Land Riding Ru
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	YAS 30 SGT
Weight / LBS	3.228
Nominal Bolt Center to Center	4.8 Inch 121 Millimeter
Bolt Spacing Maximum	5.563 Inch 141.3Millimeter
d	1.181 Inch 30 Millimeter
Bolt Spacing Minimum	3.689 Inch 93.7Millimeter
B	1.689 Inch 42.9 Millimeter
D	1.5 Inch 38.1 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
Shaft Size d	1.181 in
Bearing Type	Ball Bearing
Inside Ring Outside Diameter	1.587 in
Dimension T	0.846 in
Dimension D1	1.587 in
Series	Industrial
Weight	3.147 lb
Seal Type	Shroud Seal
Base to Center Height H	42.86 mm
Total Length L	157.2 mm



Jinan Chenyu Bearing Import & Export ...

Total Width A	1.689 in
Bolt Hole Spacing J	117.5 mm
Bolt Hole Width N	14.3 mm
Bolt Hole Length N1	23.8 mm
Foot Height H1	16.7 mm
Total Height H2	84.9 mm
Dimension L1	52.4 mm
Inside Ring Width B	=Bearings1_Inside Ring Width= mm
Center of Bearing from End S	15.9 mm
Dimension B1	1.547 in
Static Load Rating	2530 lbf
Dynamic Load Rating	4850 lbf